



## TECHNICAL SPECIFICATIONS

Engine	: 22.1 Kw (30 Hp)
Burn Cell Frequency	: 18.900 Kcal / H.
Formulation Tank	: 5.7 Lt
Fuel Tank	: 1.2 Lt.
Tank Pressure	: 0.2 Bar
Micron Sizes	: 0.5 - 50 micron sizes.
Battery	: 4 pcs. x 1.5 Volt D size alkaline batteries.
Formulation Consumption	: 0 - 42 Lt / H., 2200 cubic meters/min. (Adjustable with nozzles)
Fuel Consumption	: 1.9 Lt / H.
Weight	: 7.9 Kg.
Dimensions	: 120 cm. x 27 cm. x 34 cm. ( L x W x H )
Shipping Dimensions	: 122 cm. x 32 cm. x 43 cm. ( L x W x H )
Shipping Weight	: 12 Kg.

WHITE FOG

Street: 6169 No: 18/A Karacaoglan Mah.  
Bornova / İzmir - TURKEY  
Tel: +90 232 472 11 83  
E-mail : info@whitefog.com

[www.WhiteFog.com](http://www.WhiteFog.com)



Light weight for convenient use in areas where poor roads and tracks make it difficult to handle heavy equipment.

### Where to Use?

Fogging in agricultural and rural areas (cotes, barns, poultry houses); plant protection in greenhouses and plantations, additionally functions as an anti freezer in green houses.

Stock protection in silos, store rooms (food and agricultural products, textiles and tobacco)

Public health Vector Control (Malaria, Dengue, Chikungunya etc). Kills all the flying and crawling insects, mosquitoes.

Used at canalizations, hotels, amusement parks, golf courses, military sites, holiday camps and villages, green fields and forests, marshlands, factories, winter-summer houses. Used under municipalities public health and hygiene.

Odor control around marshlands, canalizations, wastewater-affluent, mass garbage areas.

Some superior specifications compared to other "Portable Thermal Fogging" machines ;



WHITE FOG

Street: 6169 No: 18/A Karacaoglan Mah.

Bornova / İzmir - TURKEY

Tel: +90 232 472 11 83

E-mail : info@whitefog.com

[www.WhiteFog.com](http://www.WhiteFog.com)